

BEST OF BOTH WORLDS

VeriFone's Optimum T4230 is a unique wireless device that offers GPRS connectivity in a countertop design. With a V.34 modem standard, wherever there is a power outlet the T4230 provides the benefits of a wireless connection with the assurance of a dial backup. It combines the best-of-breed features of the Optimum T4200 family in a device with optimum portability and security.

OPTIMUM T4230

Simple, Easy-To-Use Features

- Thermal printer design with clear lid alerts cashiers to low paper conditions
- Simple drop-in loading virtually eliminates paper jams and the large paper roll means more receipts between changes
- Large, ADA-style, 19-key layout allows for easy key recognition
- The Clear, Enter, Cancel and "5" keys provide tactile feedback for visually-impaired customers
- Slim form factor makes it perfect for handover installations
- Color-coded port labels simplify service and support
- Industry-leading software includes the functionality necessary to introduce value-added opportunities to merchants

Fast, Time-Saving Performance

- Graphics-capable thermal printer allows merchants to print logos and coupons directly at the point of service
- V.34 modem allows placement as a dial first – IP later and gives the assurance of dial backup to IP
- ARM9, 32-bit processor provides speed and functionality – with four times the processing power and speed of an ARM 7 processor used in competitive devices

Unsurpassed Value

- Depot-upgradeable, modular communications provide a flexible platform with investment protection and are easy to replace for faster service
- 24MB standard memory – more than competitive devices in its class – so it can easily handle software size increases as well as the addition of value-added applications
- PCI PED approved for PIN transactions
- Bright, white backlit display utilizes superior technology to achieve a sharper image for maximum visibility
- Check imagers, PIN pads and contactless check readers can be connected using the peripheral port to provide more payment choices
- Secure design meets the most stringent security regulations in the industry, including PCI PED and PTSP
- Patented architecture provides the ultimate protection against any unauthorized loading of applications



Processor

32-bit ARM9

Keypad

19 buttons; PCI PED approved;
water splash-resistant
6 navigation buttons
ADA-style markings

Display

FSTN LCD with graphics
160 x 80 resolution
White LED, backlit

Card Reader

Magnetic stripe: Bi-directional, Tracks 1, 2 & 3
Chip card: Optional; EMV4.0 Level 1 & 2, ISO 7816
Three SAM slots

Communications

Primary: 10/100Base-T Ethernet
Modem: V.34/33.6Kbps
Ports: RS-232 for peripherals, PIN port for external PIN pad

Printer

Clamshell design, drop-in loading, thermal technology, 384 dots per line
15+ lines per second
Paper roll: 2.25", 50mm diameter

Memory

Total: 24MB
Flash: 8MB
SDRAM: 16MB
SRAM (non-volatile): 512K
SRAM Backup: 5-year battery

Power

AC: 100-240V, 50/60 Hz
DC: 7.5V, 2.8A

Security

PCI PED approved
Triple DES: ANSI X9.52, PIN-ANSI X9.8, MAC-ANSI X9.9 Part 1-ANSI X9.24
Key management: DUKPT, Triple DES
DUKPT and Triple DES master/session keys

Physical

3.6 in (w) x 8.1 in (l) x 2.3 in (h)
91.44 mm (w) x 205.74 mm (l) x 58.42 mm (h)

Weight

1.06 lbs / 0.48 kg

Environment

Temperature: 0-45°C/32-115°F
Humidity: Max 85%, non-condensing
ESD: 12,000 volts

www.verifone.com

©2011 VeriFone, Inc. All rights reserved. VeriFone, the VeriFone logo and Optimum T4230 are either trademarks or registered trademarks of VeriFone in the United States and/or other countries. All other trademarks or brand names are the properties of their respective holders. All features and specifications are subject to change without notice. Reproduction or posting of this document without prior VeriFone approval is prohibited.
06/11 45962 Rev A FS

 **VeriFone**
THE WAY TO PAY™